



## COT Compact4 mobile K-WOM Thermal printer for mobile applications

- ▶ Direct thermal printer with 104 mm print width
- ▶ 8 dots/mm (203 DPI)
- ▶ Up to 152 mm/s print speed
- ▶ Rugged, industrial-grade metal case
- ▶ Stable roll holder
- ▶ Easy change of paper
- ▶ Large paper capacity by 100 mm roll diameter
- ▶ Operating at 24V dc for mobile use
- ▶ COT IAS multifunctional controller with:
  - V24 and ethernet interface, Configsaver, various data protocols and emulations
  - RPO Remote Printer Observer port for network-based printer status monitoring
  - HTTP- Server for status monitoring and configuration

The printing station COT Compact4 mobile is designed as a stand-alone print station for mobile applications. The unit is equipped with a power supply for 24 - 45 volts and has a central network switch. Thus, the printing station can be used on forklifts or other battery-powered conveyor systems. The printing station can be supplied either as a complete unit or as well as individual components (printer, voicemail). So the printing station can be optimally adapted to a stacker for example.

## Technical Specifications

Mistakes reserved

Typ	COT Compact4 mobile K-WOM
Technology	Direct thermal printing
Resolution	203 dpi, 8 Punkte/mm
Print speed (max.)	125 mm/s
Emulations	COT CFP (IGP), DPL, ZPL, BPL, IPL
Protocols	Pros, SAP, K-WOM incl. RPO-Status, SAP with zCOT Support, external entry (f.e. FTP) are User and Passwort protected
Barcodes	The most common barcodes are available, including many two-dimensional and stacked codes: QR Code, PDF 417, Data Matrix, MaxiCode, EAN 13
Media types	Roll material; endless or perforated, stickers, optional z-folded
Media sensing	Label gap, notch or reflective
Media sensor	adjustable
Media width (min. – max.)	40 - 115 mm
Media rolls size (max.)	100
Media thickness	0,058-0,18 mm
Print width (max.)	104 mm
Print length (max.)	unlimited
Label length (min.)	10 mm
Interfaces	Standard: IAS-Ethernet with Configsaver, RS232C, USB, Optional: WLAN
Size (W x D x H)	ca. 215 x 250 x 150 mm (without paper)
Weight (without paper roll)	ca. 5,4 kg
Supply voltage	24V
Power consumption (approx.)	Stand-by: 0.3 A Printing: max. 19.5 A peak



## Printers, Labels and ribbons – from one source

For our printer systems we produce all kinds of labels – paper, carton and foil – blank or preprinted, according to your individual requirements.

In addition we can provide thermal transfer ribbons (carbon ribbons) of all sizes and in different qualities, matching your specific label types.